



PO BOX 54 HAMILTON NSW 2303
140 DENISON STREET CARRINGTON NSW 2294
PH: 02 49615 777 FAX: 02 49696 246
EMAIL: newcastleminicranes@bigpond.com
ABN: 23 466 091 441

NISSHA NTC-L



Specifications

Length: 6500mm
Width: 1920mm
Height: 2650mm
Weight: 8000kg

6.2 Rated lifting load table of NTC48L

6.2.1 Rated lifting load table of NTC48L

Operating : Outriggers fully unfolded (Unit; ton) (全周吊、ton)

radius (m)	5.75 m Boom	9.5 m Boom	13.25 m Boom	17 m Boom
2.0	4.80	4.80		
2.6	4.80	4.80	2.90	
3.0	4.25	4.25	2.90	
3.5	3.59	3.59	2.90	
4.0	2.98	2.98	2.90	1.75
4.5	2.52	2.52	2.52	1.75
5.0	(4.6 m) 2.43	2.20	2.20	1.75
5.5		1.96	1.96	1.75
6.0		1.75	1.75	1.75
7.0		1.41	1.41	1.41
8.0		1.16	1.16	1.16
9.0		(8.3 m) 1.08	0.96	0.96
10.0			0.80	0.80
11.0			0.68	0.68
12.0			0.58	0.58
13.0			(12.1 m) 0.57	0.51
14.0				0.45
15.0				0.40
15.8				0.35

* The rated lifting loads in the table show the permissible lifting loads related to every operation radius with the outrigger arms fully unfolded. Unfold the outrigger arms prior to performing craning operation and input the outrigger unfolding condition into the "Moment limiter".

* The rated lifting loads in the table show under the conditions of the machine being positioned on firm and level ground, and 78% of the tipping load.

* The actual lifting load shall be the load shown in the table minus the weights of all lifting devices such as sling ropes, hooks, etc.

6.2.5 Operating range

